


Link-Belt
EXCAVATORS

355 X4S

BROCHURE






GIVE IT A SPIN

Built upon the solid foundation of our award-winning X4 Series with more capability and intriguing new features, this X4S machine is the largest minimum swing radius excavator in the Link-Belt product line with a weight of around 78,600 lbs. The 355 X4S is versatile enough to suit the expanding demands of increasingly dynamic contractors thanks to a reduced tail swing and lots of control and power. It is perfect for road building and maintenance, home excavation, site preparation, construction, sewage work, and demolition operations.







NEXT LEVEL STRENGTH



TOUGH ON DIRT, EASY ON FUEL

Link-Belt Excavators have a long history of saving you money without limiting power or productivity. That's why we run an efficient Isuzu Final Tier 4 Certified engine that delivers 205 horsepower, so you can go the distance and save on fuel. The 355 X4S features superior cycle times, lower fuel consumption, and fuel monitoring at your fingertips.



OPERATOR WORK MODE

Stay in control of fuel economy, productivity, and power depending on the task at hand.

Lifting - Lower engine speed for fine control

Eco - Lower fuel consumption

Power - Normal power mode

Speed Priority - For increased productivity

PERFORMANCE BOOST

We understand your work is essential, and we want to help you get it done right, the first time. We engineer reliability and performance into every piece of equipment, offering advanced lifting performance, pressure relief with constant boost function, preset flow rate and pressure for up to 10 attachments. With optimized pump control and engine speed, you've got unparalleled digging force and working range.



ROBUST POWER

Our exclusive flow control system starts with more digging power, increased lift capacities and rapid cycle times. Kawasaki electronically controlled pumps guarantee hydraulic flow is delivered precisely when and where it's needed. The result is more maneuverability and precision, smoother machine operation and improved fuel efficiency across all operating modes.





IN FULL SWING

When you need to get in and out of a tight spot quickly and effortlessly, rely on the 355 X4S with its minimum swing radius. A smaller swing means safer operability and extra visibility in confined work areas, such as utilities, highway construction, development, and landscaping.



ROOM TO MOVE

- 37% reduced tail swing compared to the 300 X4S
- 44% reduced tail swing compared to the 370 X4S



WELL TRAVELED

The 355 X4S is nimble and powerful, yet compact enough to be transported with relative ease. From the comforts of your cab, prioritize flow for swinging and loading, with up to 10.2 rpm.





**CLEVER
CUSTOMIZATION**



CUSTOM FLOW

The 355 X4S offers exceptional convenience and operability, integrating throttle volume and frequently used modes into a single panel. Our tailored machine function switches ensure seamless operation for digging and loading tasks. This machine provides customizable operability with four distinct work modes—lifting, eco, power, and speed priority—allowing you to prioritize flow and machine functionality from the comfort of your seat, no matter the job.

CUSTOM ATTACHMENT SETTINGS

Store and name up to 10 distinct attachment settings, customizing the flow rate and pressure you need to get the job done. With tailored attachment operations, lost time and overworking are a thing of the past.



OFFICE WITH A VIEW

The 355 X4S features one of the most spacious, technologically equipped cabs in its class. Joystick functionality and 4 power modes provide quick customization for the work at hand. Controls are always close with the armrests and joystick conveniently built into the seat height adjustment.



COMFORTS OF HOME

To reduce fatigue during long jobs, the 355 X4S features an ergonomic footrest, air suspension, heat, tilt functions, a two-step incline, and optimized foot pedal height. Four styles of superior lumbar back support ensure maximum comfort, while adjustable armrests and a recline feature up to 155 degrees provide added relaxation during breaks.

RELY ON RED

Advances in design deliver the best in comfort and safety during operation. The 355 X4S is manufactured with built-in safety features, the WAVES system, vertical wide monitor for better visibility, auto operation lever lock function and short tail with reduced swing.

• **MONITOR AND MOVE**

The 355 X4S comes equipped with a 10" HD LCD color monitor, allowing for customizable functions and increased visibility as the WAVES system provides a seamless 270° view around your machine. Check detailed fuel information and enable shortcuts for frequently used items, such as machine information, idle mode, auxiliary hydraulics, flow balance and more.

• **SAFETY**

The auto lever lock safety function prevents accidents due to unexpected operation of joystick, proportional switch, travel lever and pedal. Additional safety features include firewall, ISO-compliant guardrails, seat belt alarm, LED work lights, neutral safety start, and gate lock safety shutoff.



OPTIMIZED FUEL DELIVERY

Experience extreme force and unmatched efficiency with the Isuzu AQ-6HK1X. This Tier 4 Certified workhorse delivers robust horsepower and torque, tackling the toughest jobs effortlessly. But don't let the brute strength fool you – it's engineered for fuel efficiency with a low-maintenance after-treatment system, maximizing your bottom line and reducing downtime.





SUPPORT YOU CAN TRUST

With the purchase of a 355 X4S, you'll get expert service and support with real people. Our Customer Support staff are knowledgeable and happy to assist you with parts, service, and warranty questions.



LINK-BELT PARTS

Your Link-Belt Excavators dealer has a wide range of genuine Link-Belt parts in stock. For anything not on the shelf, our dealers have access to the Link-Belt parts depot - available for lookup online.



GROUND-LEVEL MAINTENANCE

All fuel, pilot and oil filters are in one convenient location, including a maintenance-free fuel final filter and ground level hydraulic oil sampling valve, making up keep a cinch.





WARRANTY

Our products are distinguished by a comprehensive warranty program and strict quality control. The quality and durability of the X4S are backed by a 5-year/5,000-hour full machine warranty. Additionally, our warranties are transferable, adding resale value to your equipment. Ask your local dealer about coverage options today.

HASSLE-FREE CARE

Access the radiator compartment and sample or refill hydraulic oil without the need for any tools and relieve pressure from the hydraulic tank via a handy breather cap. Whenever the cab door is opened, machine hours are displayed for 30 seconds, providing useful information when and where you need it most.





REMOTE CARE



The 355 X4S comes standard with a new dual-band modem to improve communication and functionality with greater range and real-time data capabilities.

With 24-hour RemoteCARE®, you will always know your equipment's hours, location, performance, diagnostics, and security status. Proactively monitor, plan, and address preventative maintenance items, receive machine health notifications via email, and review average fuel consumption rates for your machine right from your smartphone. Advanced security features like Geofencing, curfew settings, and theft tracking are standard with RemoteCARE®.



MINIMIZE DOWNTIME

From minor troubles caused by incorrect machine settings to advanced problem solving, we expand the range of remote support, shorten the lead time for troubleshooting, and reduce costs by moving people to and reduce costs by minimizing the need for on-site personnel.

NO SUBSCRIPTION FEES

RemoteCARE® is available with no subscription fees to the original owner and is transferable.



Scan QR code to
download RemoteCARE
app for mobile.



CUSTOMER SUPPORT JUST A CALL AWAY

Owning a Link-Belt excavator is just the beginning. A network of dedicated Link-Belt Excavator dealers stretches across the U.S. and Canada, all ready to provide you with the exceptional service you deserve. You can expect fast, dependable service whenever needed, backed by 24/7 access to parts.

No matter your location or project requirements, there's a Link-Belt dealer nearby to keep your machine running smoothly. Their expertise extends beyond just sales; they can also provide comprehensive maintenance plans, operator training, and financing options to fit your needs.



355 X4S SPECIFICATIONS

SAE Net Horsepower

205 hp (153 kW)

Operating Weight

78,600 lbs. (35,700 kg)

Swing Torque

67,900 lbf-ft (92.1 kNm)



ENGINE

Isuzu AQ-6HK1X Final Tier 4 turbocharged diesel engine with electronic control (ECM) and high pressure common-rail fuel injection, 6-cylinder, water-cooled, Cooled Exhaust Gas Recirculation (EGR), Intercooler, Variable-Geometry Turbocharger (VGT), Diesel Oxidation Catalyst (DOC) and Selective Catalytic Reduction (SCR) system with Dosing Control Module and heated DEF lines and tank. Electronic fuel pump and priming, fuel cooler, auto-idle start, auto warm-up, EPF engine protection, dual-stage fuel filtration, remote oil filter, engine oil sample port, green plug oil drain, double element air filter.

SAE J 1349 net horsepower	205 hp (153 kW) @ 1800 rpm
Displacement	475 cu in (7.8 L)
Maximum Torque	626 lbf-ft (849 Nm) @ 1500 rpm
Starter	24 V - 5.0 kW
Alternator	90 amp
Voltage	24V

CAB AND CONTROLS

ROPS and FOPS Level 1 certified with automatic climate control A/C and heat with defroster, 10" LCD Hi-Definition color monitor with customizable shortcut switches featuring a full time rear view camera display and left and right view camera, fuel efficiency gauge, custom flow control, joysticks are pre-wired for auxiliary hydraulics, knob switch customization, dual LED cab lights with programmable delay turn off, safety glass windows, sunroof with sunshade, shockless cab suspension with four fluid cab mounts, SCM High-Back reclining air-suspension seat with heat & tilt, sliding 4-position tilting control consoles, Bluetooth technology, AM/FM sound system with USB and MP3 auxiliary input jack, digital clock, dome light, seat belt, coat hook, 2 cup holders, storage compartments, floor mat, footrests, smart phone tray, 24V socket, 12V outlet, travel alarm, handrails, mirrors, side-entry cab filter, spare parts kit.

Four selectable work modes (SP, Power, Eco, & Lift), RemoteCARE telematics GPS system, anti-theft password protection system, onboard self-diagnostic system with memory and service interval reminders, auto idling system, one-touch decelerator, auto-idle engine shutdown, neutral safety start, gate-lock safety shutoff, top guard OPG level 1 in cab structure.

355 X4S SPECIFICATIONS

HYDRAULIC SYSTEM

Open-center system, (2) electronically controlled variable displacement axial piston pumps, (1) gear pump for pilot controls. Main control valve with one 4-spool valve and one 5-spool valve with auxiliary spool. Internal anti-drift valves for boom and arm, oil cooler, high performance 6-micron full flow return filter, 8-micron pilot filter, firewall and hydraulic free swing.

Hydraulic Pumps

Pump Output	2 x 64.2 gpm (243 L/min)
Pilot Pump Maximum Flow	7.1 gpm (27 L/min)

Relief Valve Settings

Boom Up / Arm / Bucket	4,970 psi (34.3 MPa)
in Power Boost	5,410 psi (37.3 MPa)
Swing Circuit	4,410 psi (30.4 MPa)
Travel Circuit	4,970 psi (34.3 MPa)

Hydraulic Cylinders

Number of Cylinders - Bore x Stroke

Boom	2 - 5.5" x 57.5" (140 mm x 1461 mm)
Arm	1 - 5.9" x 65" (150 mm x 1650 mm)
Bucket	5.3" x 42.4" (135 mm x 1078 mm)

SWING

Planetary reduction powered by axial-piston motor, internal ring gear with grease cavity for swing pinion, swing bearing is single-row, shear type ball bearing, mechanical disc swing brake, auto-power swing.

Swing Speed	10.2 rpm
Tail Swing	6'6" (1.98 m)
Swing Torque	67,900 lbf-ft (92.1 kNm)

UNDERCARRIAGE

16'4" (4.98 m) undercarriage by 8'6" (2.60 m) track gauge, sealed and strutted track chain with double track guide, sealed rollers and idlers, disc type brakes, adjustable track tension, swivel guard.

Carrier Rollers	2 per Side
Track Rollers	8 per Side
Track Link Pitch	8.5" (216 mm)
Shoes	48 per Side
Shoe Width	31.5" (800 mm)
Ground Pressure	7.3 psi (0.05 MPa)

355 X4S SPECIFICATIONS

TRAVEL SYSTEM

Two-speed independent hydraulic travel with compact axial-piston motors, hydraulic motor powered output shaft coupled to a planetary reduction drive and track sprocket, all hydraulic components mounted within the width of side frame, automatic downshift for high torque to overcome obstacles, spring-applied hydraulic release parking brake built into each motor, travel motors equipped with counterbalance valve to prevent over-speeding down an incline, single-pedal straight line travel.

Travel Speeds	1.7 - 2.7 mph (2.8 - 4.4 km/h)
Drawbar Pull	60,100 lbf (268 kN)
Gradeability	70% (35°)

ATTACHMENT

HD Boom	20' 2" (6.15 m)
Available Arms	Digging Force
10' 5" (3.18 m)	28,870 lbf (128.4 kN)
with Auto Power Boost	31,380 lbf (139.6 kN)
8' 8" (2.65 m)	33,050 lbf (147.0 kN)
with Auto Power Boost	35,950 lbf (159.9 kN)
12' 0" (3.66 m)	25,700 lbf (114.3 kN)
with Auto Power Boost	27,940 lbf (124.3 kN)
Bucket Digging Force	39,340 lbf (175 kN)
with Auto Power Boost	42,780 lbf (190.3 kN)

LUBRICANT AND COOLANT CAPACITY


Fuel Tank	100 Gallons (379 Liters)
Hydraulic System	96 Gallons (363 Liters)
Hydraulic Tank	43 Gallons (164 Liters)
Final Drive (per side)	2.5 Gallons (9.5 Liters)
Swing Drive	1.3 Gallons (5 Liters)
Engine Oil	10.8 Gallons (40.9 Liters)
DEF Tank	11 Gallons (43 Liters)
Coolant System	11.6 Gallons (43.8 Liters)

OPERATING WEIGHT

Working weight with 31.5" (800 mm) shoes, 20' 2" (6.15 m) HD boom, 10' 5" (3.18 m) arm, 2,095 lbs. (950 kg) bucket, 17,500 lbs. (7 950 kg) counterweight.	78,600 lbs. (35 700 kg)
--	-------------------------


355 X4S SPECIFICATIONS

WORKING RANGE



Machine Equipped with 20' 2" (6.15 m) HD Boom	Arm 10' 5" (3.18 m)	Arm 8' 8" (2.65 m)	Arm 12' 0" (3.66 m)
A. Maximum reach	35' 4" (10.77 m)	33' 10" (10.32 m)	36' 11" (11.26 m)
B. Maximum reach @ ground level	34' 8" (10.57 m)	33' 2" (10.11 m)	36' 4" (11.07 m)
C. Maximum dig depth	22' 10" (6.95 m)	21' 1" (6.42 m)	24' 5" (7.44 m)
D. Maximum dig height	36' 8" (11.17 m)	35' 11" (10.95 m)	37' 11" (11.56 m)
E. Maximum dump height	26' 7" (8.10 m)	25' 10" (7.87 m)	27' 10" (8.47 m)
F. Digging depth 8' (2.44 m) level bottom	22' 3" (6.79 m)	20' 6" (6.24 m)	23' 11" (7.29 m)
G. Bucket rotation	176°	176°	176°
H. Maximum vertical wall depth	19' 8" (5.99 m)	18' 6" (5.64 m)	21' 8" (6.60 m)

TRAVEL DIMENSIONS



355 X4S SPECIFICATIONS

LIFT CAPACITIES

RADIUS OF LOAD:

10' 5" (3.18 M) ARM WITH 20' 2" (6.15 M) HD BOOM WITH POWER-BOOST APPLIED

		 5' 0" (1.5 m)		 10' 0" (3.0 m)		15' 0" (4.5 m)		20' 0" (6.0 m)		25' 0" (7.5 m)		30' 0" (9.0 m)		Cap at Max. Reach	
End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side
+30' 0"	lbs													14,700*	14,700*
(9.14 m)	kg													6,665*	6,665*
+25' 0"	lbs							16,650*	16,650*					13,100*	13,100*
(7.5 m)	kgs							7,550*	7,550*					5,940*	5,940*
+20' 0"	lbs							17,500*	17,500*	16,950*	13,350			12,600*	11,750
(6.0 m)	kg							7,935*	7,935*	7,685*	6,055			5,715*	5,325
+15' 0"	lbs			33,500*	33,500*	23,900*	23,900*	19,900*	18,300	17,900*	13,050			12,600*	10,350
(4.5 m)	kg			15,195*	15,195*	10,840*	10,840*	9,025*	8,300	8,115*	5,915			5,715*	4,690
+10' 0"	lbs					30,750*	26,450	23,100*	17,400	19,450*	12,600			13,050*	9,600
(3.0 m)	kg					13,945*	11,995	10,475*	7,890	8,820*	5,715			5,915*	4,350
+5' 0"	lbs					36,250*	24,850	26,050*	16,600	19,850	12,200	14,800*	9,400	14,000*	9,350
(1.5 m)	kg					16,440*	11,270	11,815*	7,525	9,000	5,530	6,710*	4,260	6,350*	4,240
Ground	lbs					38,400*	24,100	27,200	16,050	19,500	11,850			15,500	9,550
Line	kg					17,415*	10,930	12,335	7,280	8,845	5,375			7,030	4,330
-5' 0"	lbs			25,600*	25,600*	37,800*	23,900	26,900	15,850	19,350	11,750			16,750	10,250
(1.5 m)	kg			11,610*	11,610*	17,145*	10,840	12,200	7,185	8,775	5,325			7,595	4,645
-10' 0"	lbs			41,150*	41,150*	34,800*	24,050	26,200*	15,900					19,550	11,900
(3.0 m)	kg			18,665*	18,665*	15,785*	10,905	11,880*	7,210					8,865	5,395
-15' 0"	lbs			38,400*	38,400*	28,450*	24,600	20,650*	16,350					19,650*	15,750
(4.5 m)	kg			17,415*	17,415*	12,900*	11,155	9,365*	7,415					8,910*	7,140

RADIUS OF LOAD:

8' 8" (2.65 M) ARM WITH 20' 2" (6.15 M) HD BOOM WITH POWER-BOOST APPLIED

		 5' 0" (1.5 m)		 10' 0" (3.0 m)		15' 0" (4.5 m)		20' 0" (6.0 m)		25' 0" (7.5 m)		30' 0" (9.0 m)		Cap at Max. Reach	
End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side
+25' 0"	lbs							18,650*	18,650*					16,950*	16,450
(7.5 m)	kgs							8,455*	8,455*					7,685*	7,460
+20' 0"	lbs					21,200*	21,200*	19,200*	18,800	17,700*	13,200			16,100*	12,950
(6.0 m)	kg					9,615*	9,615*	8,705*	8,525	8,025*	5,985			7,300*	5,870
+15' 0"	lbs					26,600*	26,600*	21,500*	18,150	19,150*	13,000			16,050*	11,250
(4.5 m)	kg					12,065*	12,065*	9,750*	8,230	8,685*	5,895			7,280*	5,100
+10' 0"	lbs					33,350*	26,050	24,500*	17,350	20,350	12,650			16,650*	10,400
(3.0 m)	kg					15,125*	11,815	11,110*	7,865	9,230	5,735			7,550*	4,715
+5' 0"	lbs					37,850*	24,700	27,100*	16,600	19,900	12,250			16,350	10,150
(1.5 m)	kg					17,165*	11,200	12,290*	7,525	9,025	5,555			7,415	4,600
Ground	lbs					38,750*	24,200	27,300	16,200	19,650	12,000			16,850	10,400
Line	kg					17,575*	10,975	12,380	7,345	8,910	5,440			7,640	4,715
-5' 0"	lbs			25,850*	25,850*	37,150*	24,200	27,150	16,050	19,600	11,950			18,450	11,300
(1.5 m)	kg			11,725*	11,725*	16,850*	10,975	12,315	7,280	8,890	5,420			8,365	5,125
-10' 0"	lbs			44,050*	44,050*	33,150*	24,500	25,150*	16,200					20,550*	13,400
(3.0 m)	kg			19,980*	19,980*	15,035*	11,110	11,405*	7,345					9,320*	6,075
-15' 0"	lbs					25,050*	25,050*							19,600*	18,950
(4.5 m)	kg					11,360*	11,360*							8,890*	8,595

355 X4S SPECIFICATIONS

LIFT CAPACITIES (CONT.)

RADIUS OF LOAD:

12' 0" (3.66 M) ARM WITH 20' 2" (6.15 M) HD BOOM WITH POWER-BOOST APPLIED

						5' 0" (1.5 m)		10' 0" (3.0 m)		15' 0" (4.5 m)		20' 0" (6.0 m)		25' 0" (7.5 m)		30' 0" (9.0 m)		Cap at Max. Reach	
End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side
+30' 0"	lbs											13,800*	13,800*					11,650*	11,650*
(9.14 m)	kg											6,255*	6,255*					5,280*	5,280*
+25' 0"	lbs											14,900*	14,900*	12,350*	12,350*			10,550*	10,550*
(7.5 m)	kgs											6,755*	6,755*	5,600*	5,600*			4,785*	4,785*
+20' 0"	lbs											15,900*	15,900*	15,600*	13,450			10,100*	10,100*
(6.0 m)	kg											7,210*	7,210*	7,075*	6,100			4,580*	4,580*
+15' 0"	lbs							21,350*	21,350*	18,400*	18,400*	16,750*	13,100	12,150*	9,750	10,050*	9,400		
(4.5 m)	kg							9,680*	9,680*	8,345*	8,345*	7,595*	5,940	5,510*	4,420	4,555*	4,260		
+10' 0"	lbs							28,300*	26,850	21,700*	17,500	18,450*	12,600	15,350	9,550	10,350*	8,800		
(3.0 m)	kg							12,835*	12,175	9,840*	7,935	8,365*	5,715	6,960	4,330	4,690*	3,990		
+5' 0"	lbs							34,450*	25,000	24,950*	16,600	19,800	12,100	15,100	9,300	11,000*	8,550		
(1.5 m)	kg							15,625*	11,335	11,315*	7,525	8,980	5,485	6,845	4,215	4,985*	3,875		
Ground	lbs			14,550*	14,550*	37,650*	23,950	27,100	15,950	19,400	11,750	14,900	9,100	12,100*	8,700				
Line	kg			6,595*	6,595*	17,075*	10,860	12,290	7,230	8,795	5,325	6,755	4,125	5,485*	3,945				
-5' 0"	lbs	15,300*	15,300*	23,700*	23,700*	37,950*	23,600	26,700	15,600	19,150	11,500					13,950*	9,250		
(1.5 m)	kg	6,935*	6,935*	10,750*	10,750*	17,210*	10,700	12,110	7,075	8,685	5,215					6,325*	4,195		
-10' 0"	lbs	25,200*	25,200*	35,900*	35,900*	35,800*	23,650	26,650	15,600	19,150	11,550					17,350	10,550		
(3.0 m)	kg	11,430*	11,430*	16,280*	16,280*	16,235*	10,725	12,085	7,075	8,685	5,235					7,865	4,785		
-15' 0"	lbs			42,700*	42,700*	30,700*	24,100	22,800*	15,900							18,600*	13,300		
(4.5 m)	kg			19,365*	19,365*	13,925*	10,930	10,340*	7,210							8,435*	6,030		

355 X4S SPECIFICATIONS

LIFT CAPACITIES (CONT.)

RADIUS OF LOAD:

10' 5" (3.18 M) HD ARM WITH 20' 2" (6.15 M) HD HD BOOM WITH POWER-BOOST APPLIED

				5' 0" (1.5 m)		10' 0" (3.0 m)		15' 0" (4.5 m)		20' 0" (6.0 m)		25' 0" (7.5 m)		30' 0" (9.0 m)		Cap at Max. Reach	
End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side	End	Side
+30' 0"	lbs															14,600*	14,600*
(9.14 m)	kg															6,620*	6,620*
+25' 0"	lbs									16,400*	16,400*					13,000*	13,000*
(7.5 m)	kgs									7,435*	7,435*					5,895*	5,895*
+20' 0"	lbs									17,250*	17,250*	16,650*	13,100			12,450*	11,500
(6.0 m)	kg									7,820*	7,820*	7,550*	5,940			5,645*	5,215
+15' 0"	lbs					33,100*	33,100*	23,550*	23,550*	19,600*	18,050	17,600*	12,800			12,450*	10,100
(4.5 m)	kg					15,010*	15,010*	10,680*	10,680*	8,890*	8,185	7,980*	5,805			5,645*	4,580
+10' 0"	lbs							30,350*	26,100	22,750*	17,150	19,150*	12,350			12,900*	9,350
(3.0 m)	kg							13,765*	11,835	10,315*	7,775	8,685*	5,600			5,850*	4,240
+5' 0"	lbs							35,800*	24,400	25,650*	16,300	19,600	11,900	14,650*	9,150	13,850*	9,100
(1.5 m)	kg							16,235*	11,065	11,630*	7,390	8,890	5,395	6,645*	4,150	6,280*	4,125
Ground	lbs							37,900*	23,600	26,850	15,700	19,200	11,550			15,250	9,250
Line	kg							17,190*	10,700	12,175	7,120	8,705	5,235			6,915	4,195
-5' 0"	lbs					25,500*	25,500*	37,300*	23,400	26,550	15,450	19,050	11,450			16,450	10,000
(1.5 m)	kg					11,565*	11,565*	16,915*	10,610	12,040	7,005	8,640	5,190			7,460	4,535
-10' 0"	lbs					41,000*	41,000*	34,300*	23,600	25,800*	15,550					19,250	11,600
(3.0 m)	kg					18,595*	18,595*	15,555*	10,700	11,700*	7,050					8,730	5,260
-15' 0"	lbs					37,850*	37,850*	28,000*	24,200	20,250*	16,050					19,250*	15,450
(4.5 m)	kg					17,165*	17,165*	12,700*	10,975	9,185*	7,280					8,730*	7,005

NOTES: EXCAVATOR LIFTING CAPACITIES

- The lift capacities above are based on the ISO standard, ISO 10567:2007 -"Earthmoving Machinery - Hydraulic Excavators - Lift Capacity"
- Lifting capacities shown should not be exceeded. The weight of all lifting accessories must be deducted from the above lifting capacities. The use of a work tool attachment point as the lift point could affect the machine lift performance.
- Lifting capacities are based on the machine standing on a firm, uniform supporting surface. Users must make allowances for job conditions such as soft or uneven ground.
- Lifting capacities shown do not exceed 75% of the minimum tipping loads or 87% of the hydraulic capacities. Lifting capacities marked with an asterisk (*) are limited by hydraulic capacities.
- The least stable position is lifting over the side.
- Operators should be fully acquainted with the Operator's Manual & Operating Safety Booklet, furnished by LBX Company LLC before operating the machine.
- Lift capacities apply only to the machine as originally manufactured and normally equipped by LBX Company LLC.
- This lift chart is without bucket.

355 X4S SPECIFICATIONS

STANDARD EQUIPMENT

CAB

- 270° WAVES Camera System
- 12V Power Outlet
- AM/FM Sound System
- Anti-Theft Device
- Auxiliary Switches on Control Lever
- Cab Air Filter - External
- Cab Handrails
- Cab Interior Light
- Cab ISO-Mounts
- LED Cab Lights
- Clear Roof Window
- Climate Control A/C and Heater
- Cup Holder
- Defroster
- Digital Clock
- Emergency Exit and Hammer
- Face Vent
- Floor Mat (Split)
- Front Window One-Touch Lock
- Gate Lock Hydraulic Activation
- Horn
- Hour Meter (Digital)
- LCD 10" Color Monitor
- Magazine Storage Rack
- Maintenance Interval Reminders
- MP3 Auxiliary Input Jack
- On-Board Diagnostic System
- One-Piece Right Window
- Radio Mute Switch
- Rear View Camera
- Rear View Mirrors (3)
- RemoteCARE Support System (GPS)
- Roof Sun Shade
- ROPS Certified

Structure

- Safety Glass Windows
- SCM Air-Suspension Seat with Tilt & Heater
- Seat Recline
- Selectable Monitor Languages
- Side View Camera (2)
- Small Storage
- Smart Phone Tray
- Travel Alarm with Cancel Switch
- Trip Meter (Digital)
- Wiper & Washer
- Wiper Switch on RH Joystick

ENGINE

- 90A Alternator
- Air Filter (Double Element)
- Air Filter Restriction Indicator
- Auto Warm-Up System
- Auto-Idle
- Auto-Idle Engine Shutdown
- Battery Disconnect Switch
- Cooling Fan
- Diesel Oxidation Catalyst (DOC)
- Drain for Fuel Tank
- Dual Remote Fuel Filters with Water Separators
- EGR Coolers
- Emergency Engine Stop
- Engine Oil Sample Port
- Engine Protection Feature
- External Fuel Gauge
- External DEF Gauge
- Fan Housing
- Fuel Cooler
- Fuel Filter Restriction Indicator

- Fuel Management System
- Fuel Usage History
- Fuel Usage Monitor
- Glow Plug Pre-Heat
- Idle-Start
- Intercooler
- Neutral Start
- One-Touch Idle
- Radiator / Oil Cooler / Intercooler Protective Screen
- Remote Engine Oil Drain
- Remote Oil Filter
- Selective Catalytic Reduction (SCR)
- DEF Gauge on Monitor
- VGT Turbocharger

HYDRAULICS

- Anti-drift valves (Arm & Boom)
- Arm Regeneration
- Arm Speed Assistance (2 Pump Flow)
- Attachment Cushion Valve
- Auto Swing Priority
- Custom Flow Control
- Auxiliary Tool Settings (Custom Naming)
- Auxiliary Valve
- Boom Regeneration
- Boom Speed Assistance (2 Pump Flow)
- Bucket Curl Assist
- Control Levers Pre-Wired for Auxiliary Hyd.
- Pattern Control Valve (2 way)
- Electronically Controlled Hydraulic Pumps
- Fire Wall
- Free Swing
- Hydraulic Filter

Restriction Indicator

- Hydraulic Oil Sample Port
- Long Life Hydraulic Oil (5,000 Hour)
- Neutral Pump De-Stroke
- Oil Cooler
- Power Boost
- Power Save
- Pressure Reading on Monitor
- Pump Stand-By Pressure
- Single Pedal Travel

UNDERCARRIAGE

- 800 mm shoes (31.5 in) 3-Bar Steel
- Double Track Guide
- Lashing Points (Tie-Downs)
- Sealed Link Chain
- Steps
- Strutted Track Chain
- Swivel Guard

UPPERSTRUCTURE

- Center Cover (Over Main CV)
- Fuel Tank Belly Pan
- ISO Guard Rails
- Lockable Fuel Cap and Service Doors
- Lockable Tool Box
- Tool Box Light

ATTACHMENT

- 10' 5" (3.18 m) Arm
- 20' 2" (6.15 m) HD Boom
- Auxiliary Pipe Brackets
- LED Boom Light
- Chrome Pins
- HD Bucket Linkage
- Teardrop Pin Retention Keepers

355 X4S SPECIFICATIONS

OPTIONAL EQUIPMENT

CAB

- Cab Sun Visor (Front)
- FOPS Head Guard (Level 2)
- Front Guard (Mesh)
- Front Guard (OPG Level 1)
- Front Guard (OPG Level 2)
- LED Lights for WAVES Cameras
- Rain Deflector
- Vandal Cover (Front Window)

ENGINE

- Reversible Cooling Fan

HYDRAULICS

- Hose Burst Check Valve

AUXILIARY HYDRAULIC OPTIONS

- Multi-Function Aux. w/ in-cab Pressure Settings and RH Proportional Joystick
- Combination Aux. w/ in-cab Pressure Settings and LH/RH Proportional Joystick

UNDERCARRIAGE

- 700 mm shoes (27.5 in) 3-Bar Steel
- 850 mm shoes (33.4 in) 3-Bar Steel
- Full Track Guide

ATTACHMENT

- 8' 8" (2.65 m) HD Arm
- 12' 0" (3.66 m) Arm
- 10' 5" (3.18 m) HD Arm

BUCKET SIZES



Scan the QR code to find the right size bucket, thumb, and coupler combination for the 355 X4S.

Or visit qrco.de/bcYXH5





Link-Belt[®]

EXCAVATORS

LBX Company
lbxco.com

For more information
- including a digital
version of this
brochure - scan the
QR code.



#LBX2537 • 1/25

LBX[®] and Link-Belt[®] are registered trademarks. Copyright 2025. All rights reserved. We are constantly improving our products and therefore reserve the right to change designs and specifications.